

# Asphalt Paver Best Management Practices



Presented by  
Dave King,  
Caterpillar

**FABICK** **CAT**







- SIX SIGMA
- LEAN
- TPS/CPS
- BIQ
- Ect., Ect.

All of this exists to drive consistency into process.

When we do something consistently, we can quickly and easily identify “Out of Process” and correct and eliminate.

**Bi-Product: QUALITY**



# Process Consistency = Quality

Tony Gwynn



## What

- **8 Batting Titles**
- **15 All-Star Games**
- **.338 Lifetime** (Highest since Ted Williams .344)
- **.300+ 19 of 20 Seasons**
  - .394 in 1994 (T.Williams .406, 1941)
- **Strikeouts:** 434 in 10,232 AB's
  - 1995 – 15K's (535 AB's)
  - Against HOF'rs Maddux, Glavine & Smoltz 3 SO's in 242 AB's (.331 B.A.) [Lifetime SO's Combined 9,061]
- **2024** – Bobby Witt .332/106K's, Aaron Judge .322/171

## How

- **Video Analysis** – 1<sup>st</sup> in MLB
  - Pitcher Tendencies, Focus on Mechanics
- **Attention to Detail**
  - Strike Zone Mastery, Tailored approach
- **Batting Practice**
  - High-Quality Reps, Situation Drills
- **Mastery of Adjustments**
  - 2 Strike Approach, Using the whole field
- **Fitness:**
  - Hand-Eye, Agility conditioning
- **Love of the game**



# Role of the Paver




- To meet specifications for grade, texture & smoothness





# Understanding the Paver



## ■ TRACTOR

- Pushes Truck
- Tows Screed
- Receives and feeds mix to screed

## ■ SCREED


- Floats on Mix
- Free to rise & fall

- Constant line of pull when set up properly



# TRACTOR


## Material Feed System



1. Hopper
2. Feeder bars
3. Adjustable height augers
4. Feeder sensors (Not Shown)



# Free Floating Screed




- Principle has not changed since Barber-Greene commercialized the free-floating screed in 1934




# Front-mount and Rear-mount Screeds

Front-mount




Rear-mount




Direction  
of paving





- Screed position determines mat thickness
- Screed position is constant as long as all factors remain constant






- Paving speed
- Head of material
- Screed adjustments
- Mix design
- Mix temperature
- Air temperature
- Grade temperature



# Factors Affecting Screed – Crew Controls



**1. Speed**

**2. Head of Material**


**3. Screed Adjustments**

- **Shear factor is constant**
- **Depth remains constant**




# Angle of Attack

- Angle of attack is the relationship between the nose of the screed & the grade
- Nose up attitude



# Screed Adjustments

## Angle of Attack



3mm ( $\frac{1}{8}$  in) – 6mm ( $\frac{1}{4}$  in)

- Normally 3 mm ( $\frac{1}{8}$  in) to 6 mm ( $\frac{1}{4}$  in)
- Angle too high, screed compacting with trailing edge
- Angle too low increases shear factor and wear




# How to Adjust Mat Thickness & Slope

- Use depth control cranks or “screws”
- Use tow points



# Screed Adjustments

## Increase Angle of Attack




- More material passes under screed
- Screed rises to new level
- As screed climbs, angle of attack decreases
- Re-establish same angle, but at increased depth
- Remember, screed travels through arc and reaches equilibrium @ new thickness



# Screed Adjustments

## Screed Reaction Time



- Screed reacts to change in angle of attack over 5 tow arm lengths
- 65% of change occurs in the first tow arm length
- 35% of change occurs in the last 4 tow arm lengths
- Factor improves rideability

My Chats Settings Public Chats

Logout



What are the 5 most common mistakes when it asphalt paver best management practices

## Referenced Documents (47)

Answers are supported by relevant documents. Click on here to explore them.

Asphalt paving involves a series of precise actions and techniques to ensure a high-quality, durable pavement. Here are five common mistakes related to best management practices for asphalt pavers:

### 1. Neglecting Equipment Maintenance:

- **Mistake:** Failing to regularly check and maintain the paver and related equipment.
- **Impact:** Equipment that is not well-maintained can lead to operational issues, impacting the quality of the paving process. Regular checks and maintenance are necessary to ensure equipment operates smoothly and efficiently.

### 1. Improper Joint Construction:

- **Mistake:** Not constructing longitudinal and transverse joints correctly.
- **Impact:** Poorly constructed joints can lead to weak spots, cracks, and water infiltration. Proper techniques should be used to ensure joints are well-compacted and aligned with the correct overlap and density.

### 1. Inconsistent Paver Speed:

- **Mistake:** Allowing the paver to start and stop frequently or varying the paver speed too much.
- **Impact:** This can lead to uneven surfaces, bumps, and inconsistent mat density. The paver should be operated at a steady pace to ensure a smooth and uniform surface.

### 1. Improper Material Flow:

- **Mistake:** Failing to maintain a consistent head of material in front of the screed.
- **Impact:** Inconsistent material flow can cause segregation and uneven density, leading to rough surfaces. Ensuring a constant supply of material to the augers helps in maintaining a uniform mat.

### 1. Inadequate Compaction:

- **Mistake:** Failing to achieve the required level of compaction during the paving process.
- **Impact:** Insufficient compaction can lead to air voids, reduced pavement strength, and increased permeability, which can cause premature deterioration. It's essential to follow proper rolling patterns and use the right type of rollers to achieve optimal compaction.

By addressing these key areas, paving crews can enhance the quality and durability of asphalt pavements.

New chat

Ask any asphalt pavement question.



Use custom instructions ? ☒



# Project Planning — “How Are we Getting Paid \$”

- Asphalt tonnage
- Paving width
- Specifications
- Grade Conditions







# Equipment Maintenance



- Must be free to rotate about pivot points
- Strike off and nose bar must be clean
- End gate springs clean and free







- Pivot points must be free to rotate for thickness changes to occur smoothly and for the screed to “float” relaxed
- When pins are plugged, we compensate & wear the screed out
- Smoothness suffers



# Equipment Maintenance

Clean pivot points allow smooth changes



**View looking down on top of pivot point**



**Remove side cover**




**Clean hardened mix out**



# Equipment Maintenance

## Strike Off Plate & Nose Bar







## PAVING BY THE NUMBERS

1. Heat the screed
2. Set the tow points
3. Set paving width
4. Set crown
5. Set extender height
6. Set extender slope
7. Lower screed and remove slack
8. Null the screed
9. Position end gates
10. Set auger height
11. Position feeder sensors
12. Set feeder controls
13. Fill auger chamber/place in auto
14. Set accessory functions
15. Pull off starting reference



QEXQ1403-04  
(Replaces QEXQ1403-03)

© Caterpillar 2014  
All rights reserved.





- Is this a good place to start?



- **Cut straight starting joint**
- **Butt joint flat**



- **Tack butt joint**
- **Clean area where screed will set down**







- Support full length of screed & extensions
  - 3 to 4 feet long boards
- Calculate thickness of starter boards
  - General rule vibratory screed:  $\frac{1}{4}$ " compaction per 1" loose depth
  - Example: Place 2- $\frac{1}{2}$ " loose to end up with 2" after rolling

# Joint Construction

# Boards must support Main & Extenders



**Full Support Main & Extenders**



**Screed will drop or 'nose over'**






- **No starter boards!**
- **What's going to happen?**



- Nulling the screed removes all the tension in the screed
- Use depth screws on each side until no tension is felt
- Go to tension both sides
- The screed must be “free-floating” on the mix



**ESTABLISH EXTENDER HEIGHT**



# Paver Speed


## Planning a Balanced Paving Operation



- Goal is non-stop paving
- Set to match mix delivery
- Balance with rollers
- Quick starts/stops
- 60 fpm maximum








### Pre- paving planning

- Tons per day
- Number of trucks needed
- Paver speed
- Roller speed
- Rolling Pattern
  - Density
  - Smoothness


### Tools available

- NAPA IS-120
- Paving Production Calculator App
- PaveCool App




# Paver Speed

# Changes in Paver Speed



**Increased Speed**

- Shear factor decreases
- Depth decreases



**Decreased Speed**

- Shear factor increases
- Depth increases



- Do not panic
- Stay with the plan
- Get rid of trucks in an orderly fashion
- Establish a uniform trucking pattern
- Will help density & smoothness






### Pull Off Starting Boards

- ✓ Pave mode (1), Screed in Float (2), throttle (3)
- ✓ Turn speed dial (4) to desired target speed (5) brake released (6)
- ✓ Move propel lever full forward (7)



# Paver Speed

## Quick Starts & Stops – Head of Material



- Changes in paving speed may require feeder system adjustments



- Too often, paver speed changes, but feeder system ratio dials or flow gates are not adjusted to match new paver speed to maintain 20 - 40 rpm auger speed





# Paver Speed

## Paver Stops & Starts...




- Smoothness issue
  - Will it roll out?
- Non-uniform compaction
  - Temperature differentials
- Inefficient trucking?
- Stops > 6 min = bump



# Paver Speed


# Paver Stops - density & smoothness








- MTVs can help
  - Non-stop between trucks
- Approximately 15% improved smoothness



## Head of Material Decreases

- Resistance decreased
- Depth decreases




## Head of Material Increases

- Resistance increased
- Depth increases






1. Ratio dials (or flow gates)
2. Auger height
3. Feed sensor position
4. Auger speed







- Material level at center of auger chamber
- Material level in center area controls auger speed
- Flow gates on some pavers





- Start at 2" above level of mat
- Adjust up or down depending on mix type and appearance of mat

**10" + mat thickness = auger height**





- Mechanical or sonic
- Control level of material
- Position Sensor 18" from end of augers





- 18" from mix
- 18" from last auger segment
- Working range is 12" – 32"







- Conveyor speed too fast
- WHY?
- Do we get density here?  
Smoothness?





- Auger speed uniform
- 20-40 rpm
- 2s per revolution
- Auger speed too high or too low can cause stripes in the mat







# Material Management

# Auger Extensions & Tunnels




- Fixed width paving
- Variable width paving
- Front-mount screeds
- Rear-mount screeds





# Material Management

## Front-mount Screeds



**18" with front-mount**



# Material Management

# Rear-mount Screeds




**36" with rear-mount**



# Material Management

# Always Extend Tunnel in front of Augers







- Auger extensions & tunnels to minimum width
- Be prepared to shovel as needed at wider widths



## Four step procedure

1. Release truck
2. Continue paving
3. Pave & fold wings
4. Stop quickly











- Potholes
- Density problem
- Smoothness problem



# Material Management


Spills on grade are BIG mistakes!



**Low Density**

**New AC**

**Existing**





# Material Management

# Trucks Bumping the Paver





# Material Management

# Defects Related to Truck Exchange







# Compaction

## Cat<sup>®</sup> SDX Screed Plate System







## **INNOVATIVE MATERIAL FLOW**

- Angular surface provides a kneading action as mix passes through the diamond channels
- Tapering flat surface at the back of the plates provides a smooth finished surface
- Confined mixing manipulates the aggregates to reduce air voids and increase density
- Manipulation of aggregates helps create a more uniform surface texture
- Optimized aggregate structure promotes surface temperature uniformity for more consistent compaction
- Minimizes roller shoving for better smoothness
- Increased stiffness strengthens unconfined edges, promotes better joint matching





## **INCREASED DENSITY AND SMOOTHNESS**

- IRI reductions up to 10 inches per lane mile have been realized
- Densities reaching up to 91% and higher behind the screed has led to fewer compaction passes, and in some cases, the elimination of an asphalt roller
- Lower standard deviation in density has led to increased bonus opportunities
- Increased stiffness leads to better longitudinal edge profiles and higher joint densities due to less lateral movement of the mix under the drums



# Compaction



Caterpillar: Confidential Green

# SDX Paver and screed setup





# Compaction

Before rolling

After rolling

Consistent density






- Hwy 92 near Independence, MN
- Lines are still visible, but generally less prevalent after some traffic



# States where SDX has been used shown in yellow






# Consistency & Communication are the Keys to Success!

- **Quality is the Bi-Product of Consistency**
- **Do the fundamentals right**
- **Avoid BIG mistakes**

We use the same equipment - we just need to *plan ahead* and *communicate*!





# Thank you!

For more information:

- Dave King, Caterpillar
  - King\_david\_a@cat.com
  - 763-412-5553 (mobile)
- For more information on SDX Screed Plate System, please [click here](#) or visit:



Scan me for SDX information

# Thank-you for your attention! Questions?



© 2024 Caterpillar All Rights Reserved

Materials and specifications are subject to change without notice.

Featured machines in photography may include additional equipment for special applications.

CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

